

國立臺灣科技大學

八十九學年度碩士班招生考試試題

系所組別：機械工程系丙組

科目：熱力學

(每題 20 分，第一、二、及四題所需資料列於後)

1. Consider a well-insulated piston-cylinder device that contains 4 kg of liquid water and 1 kg of water vapor at 120°C and is maintained at constant pressure. Now a 6-kg copper block at 30°C is dropped into the cylinder. Determine (a) the equilibrium temperature inside the cylinder once thermal equilibrium is established, and (b) the mass of the water vapor at the final state. (The specific heat of copper is $0.391 \text{ kJ/kg}\cdot^{\circ}\text{C}$.)
2. An insulated 5-m^3 rigid tank contains air at 500 kPa and 57°C . A valve connected to the tank is now opened, and air is allowed to escape until the pressure inside drops to 200 kPa. The air temperature during this process is maintained constant by an electric resistance heater placed in the tank. Determine (a) the electric work done during this process and (b) the total entropy change for this process. (The gas constant of air, $R = 0.287 \text{ kPa}\cdot\text{m}^3/\text{kg}\cdot\text{K}$. The specific heats of air are not constant in this problem.)
3. An air-standard cycle with *constant specific heats* is executed in a closed system with 0.002 kg of air, and it consists of the following three processes:
 - 1 – 2 Isentropic compression from 100 kPa and 27°C to 700 kPa
 - 2 – 3 $P = \text{constant}$ heat addition to initial specific volume
 - 3 – 1 $v = \text{constant}$ heat rejection to initial state
 - (a) Show the cycle on $P-v$ and $T-s$ diagrams.
 - (b) Calculate the maximum temperature in the cycle.
 - (c) Determine the thermal efficiency.
 (The specific heats of air are $C_p = 1.005 \text{ kJ/kg}\cdot\text{K}$, $C_v = 0.718 \text{ kJ/kg}\cdot\text{K}$.)
4. A hollow cylinder with inner and outer radii of R_1 and R_2 , respectively, is covered with a layer of insulation having an outer radius of R_3 . The temperature at the inner face of the cylinder (i.e. at $r = R_1$) is T_1 and the temperature at $r = R_3$ is T_3 . The thermal conductivities for the cylinder and the insulation are k_c and k_i , respectively. Assuming perfect thermal contact between the cylinder and the insulation, derive the expressions for (a) the temperature distribution in the cylinder, (b) the temperature distribution in the insulation and (c) the interface temperature.



國立臺灣科技大學
八十九學年度碩士班招生考試試題

系所組別：機械工程系丙組

科目：熱力學

5. Answer the following questions concisely. (每小題 4 分)
- (a) How does the science of heat transfer differ from the science of thermodynamics?
 - (b) How does transient heat conduction differ from steady conduction?
 - (c) How does heat conduction differ from convection? How does natural convection differ from forced convection?
 - (d) What are the three modes of heat transfer? Can they occur simultaneously (in parallel) in a medium?
 - (e) Explain how the fins enhance heat transfer from a surface. Also explain how the addition of fins may actually decrease heat transfer from a surface.



國立臺灣科技大學
八十九學年度碩士班招生考試試題

系所組別：機械工程系丙組
科目：熱力學

The general form of the conduction equation in cylindrical coordinates is

$$\frac{1}{r} \frac{\partial}{\partial r} \left(r \frac{\partial T}{\partial r} \right) + \frac{1}{r^2} \frac{\partial^2 T}{\partial \phi^2} + \frac{\partial^2 T}{\partial z^2} + \frac{q_G}{k} = \frac{1}{\alpha} \frac{\partial T}{\partial t}$$

where q_G is the rate of heat generation per unit volume.

k is the thermal conductivity.

α is the thermal diffusivity.

Saturated water—Temperature table

Temp., T , °C	Sat. press., P_{sat} , kPa	Specific volume, m^3/kg		Internal energy, kJ/kg			Enthalpy, kJ/kg			Entropy, kJ/(kg · K)		
		Sat. liquid, v_f	Sat. vapor, v_g	Sat. liquid, u_f	Evap., u_{fg}	Sat. vapor, u_g	Sat. liquid, h_f	Evap., h_{fg}	Sat. vapor, h_g	Sat. liquid, s_f	Evap., s_{fg}	Sat. vapor, s_g
0.01	0.6113	0.001000	206.14	0.0	2375.3	2375.3	0.01	2501.3	2501.4	0.000	9.1562	9.1562
5	0.8721	0.001000	147.12	20.97	2361.3	2382.3	20.98	2489.6	2510.6	0.0761	8.9496	9.0257
10	1.2276	0.001000	106.38	42.00	2347.2	2389.2	42.01	2477.7	2519.8	0.1510	8.7498	8.9008
15	1.7051	0.001001	77.93	62.99	2333.1	2396.1	62.99	2465.9	2528.9	0.2245	8.5569	8.7814
20	2.339	0.001002	57.79	83.95	2319.0	2402.9	83.96	2454.1	2538.1	0.2966	8.3706	8.6672
25	3.169	0.001003	43.36	104.88	2304.9	2409.8	104.89	2442.3	2547.2	0.3674	8.1905	8.5580
30	4.246	0.001004	32.89	125.78	2290.8	2416.6	125.79	2430.5	2556.3	0.4369	8.0164	8.4533
35	5.628	0.001006	25.22	146.67	2276.7	2423.4	146.68	2418.6	2565.3	0.5053	7.8478	8.3531
40	7.384	0.001008	19.52	167.56	2262.6	2430.1	167.57	2406.7	2574.3	0.5725	7.6845	8.2570
45	9.593	0.001010	15.26	188.44	2248.4	2436.8	188.45	2394.8	2583.2	0.6387	7.5261	8.1648
50	12.349	0.001012	12.03	209.32	2234.2	2443.5	209.33	2382.7	2592.1	0.7038	7.3725	8.0763
55	15.758	0.001015	9.568	230.21	2219.9	2450.1	230.23	2370.7	2600.9	0.7679	7.2234	7.9913
60	19.940	0.001017	7.671	251.11	2205.5	2456.6	251.13	2358.5	2609.6	0.8312	7.0784	7.9096
65	25.03	0.001020	6.197	272.02	2191.1	2463.1	272.06	2346.2	2618.3	0.8935	6.9375	7.8310
70	31.19	0.001023	5.042	292.95	2176.6	2469.6	292.98	2333.8	2626.8	0.9549	6.8004	7.7553
75	38.58	0.001026	4.131	313.90	2162.0	2475.9	313.93	2321.4	2635.3	1.0155	6.6669	7.6824
80	47.39	0.001029	3.407	334.86	2147.4	2482.2	334.91	2308.8	2643.7	1.0753	6.5369	7.6122
85	57.83	0.001033	2.828	355.84	2132.6	2488.4	355.90	2296.0	2651.9	1.1343	6.4102	7.5445
90	70.14	0.001036	2.361	376.85	2117.7	2494.5	376.92	2283.2	2660.1	1.1925	6.2866	7.4791
95	84.55	0.001040	1.982	397.88	2102.7	2500.6	397.96	2270.2	2668.1	1.2500	6.1659	7.4159
Sat. press., MPa												
100	0.10135	0.001044	1.6729	418.94	2087.6	2506.5	419.04	2257.0	2676.1	1.3069	6.0480	7.3549
105	0.12082	0.001048	1.4194	440.02	2072.3	2512.4	440.15	2243.7	2683.8	1.3630	5.9328	7.2958
110	0.14327	0.001052	1.2102	461.14	2057.0	2518.1	461.30	2230.2	2691.5	1.4185	5.8202	7.2387
115	0.16906	0.001056	1.0366	482.30	2041.4	2523.7	482.48	2216.5	2699.0	1.4734	5.7100	7.1833
120	0.19853	0.001060	0.8919	503.50	2025.8	2529.3	503.71	2202.6	2706.3	1.5276	5.6020	7.1296
125	0.2321	0.001065	0.7706	524.74	2009.9	2534.6	524.99	2188.5	2713.5	1.5813	5.4962	7.0775
130	0.2701	0.001070	0.6685	546.02	1993.9	2539.9	546.31	2174.2	2720.5	1.6344	5.3925	7.0269
135	0.3130	0.001075	0.5822	567.35	1977.7	2545.0	567.69	2159.6	2727.3	1.6870	5.2907	6.9777
140	0.3613	0.001080	0.5089	588.74	1961.3	2550.0	589.13	2144.7	2733.9	1.7391	5.1908	6.9299
145	0.4154	0.001085	0.4463	610.18	1944.7	2554.9	610.63	2129.6	2740.3	1.7907	5.0926	6.8833
150	0.4758	0.001091	0.3928	631.68	1927.9	2559.5	632.20	2114.3	2746.5	1.8418	4.9960	6.8379



國立臺灣科技大學

八十九學年度碩士班招生考試試題

系所組別：機械工程系丙組

科 目：熱力學

Ideal-gas properties of air

T K	h kJ/kg	P _r	u kJ/kg	v _r	s ^o kJ/(kg·K)
200	199.97	0.3363	142.56	1707.0	1.29559
210	209.97	0.3987	149.69	1512.0	1.34444
220	219.97	0.4690	156.82	1346.0	1.39105
230	230.02	0.5477	164.00	1205.0	1.43557
240	240.02	0.6355	171.13	1084.0	1.47824
250	250.05	0.7329	178.28	979.0	1.51917
260	260.09	0.8405	185.45	887.8	1.55848
270	270.11	0.9590	192.60	808.0	1.59634
280	280.13	1.0889	199.75	738.0	1.63279
285	285.14	1.1584	203.33	706.1	1.65055
290	290.16	1.2311	206.91	676.1	1.66802
295	295.17	1.3068	210.49	647.9	1.68515
300	300.19	1.3860	214.07	621.2	1.70203
305	305.22	1.4686	217.67	596.0	1.71865
310	310.24	1.5546	221.25	572.3	1.73498
315	315.27	1.6442	224.85	549.8	1.75106
320	320.29	1.7375	228.42	528.6	1.76690
325	325.31	1.8345	232.02	508.4	1.78249
330	330.34	1.9352	235.61	489.4	1.79783
340	340.42	2.149	242.82	454.1	1.82790
350	350.49	2.379	250.02	422.2	1.85708
360	360.58	2.626	257.24	393.4	1.88543
370	370.67	2.892	264.46	367.2	1.91313
380	380.77	3.176	271.69	343.4	1.94001
390	390.88	3.481	278.93	321.5	1.96633
400	400.98	3.806	286.16	301.6	1.99194
410	411.12	4.153	293.43	283.3	2.01699
420	421.26	4.522	300.69	266.6	2.04142
430	431.43	4.915	307.99	251.1	2.06533
440	441.61	5.332	315.30	236.8	2.08870

